



APC NetShelter™ 9000 Stromverteilereinheit (PDU) 24 AC-Ausgänge 0U Schwarz

Marke : APC

Artikel-Code: APDU9941

Produktname : NetShelter™ 9000

APC NetShelter™ 9000. PDU-Typen: Geändert, Rack-Kapazität: 0U, Typ: Einphasig. Anzahl der AC-Ausgänge: 24 AC-Ausgänge, AC-Steckertypen: C13-Koppler, C15-Koppler, C19-Koppler, C21-Koppler, Stecker: NEMA L6-30P. Kabellänge: 3 m. Nominale Eingang Spannung: 208; 200 V, Stromstärke (maximal): 30 A, Nominale Ausgang Spannung: 200 - 208 V. Konformitätsbescheinigungen: RoHS, REACH, WEEE, Zertifizierung: cUL listed; FCC part 15 class A; PSE




Design		Betriebsbedingungen	
PDU-Typen *	Geändert	Relative Luftfeuchtigkeit in Betrieb	5 - 95%
Typ	Einphasig	Höhe bei Betrieb	0 - 3048 m
Rack-Kapazität *	0U	Höhe bei Lagerung	0 - 15240 m
Montage	Senkrecht	Gewicht und Abmessungen	
Produktfarbe	Schwarz	Breite	55 mm
Anschlüsse und Schnittstellen		Tiefe	46 mm
Anzahl der AC-Ausgänge *	24 AC-Ausgänge	Höhe	1829 mm
Stecker	NEMA L6-30P	Gewicht	8,5 kg
AC-Steckertypen *	C13-Koppler, C15-Koppler, C19-Koppler, C21-Koppler	Lieferumfang	
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1	Betriebsanleitung	✓
Eingang Verbindungstyp	NEMA L6-30P	Verpackungsdaten	
Merkmale		Paketgewicht	10 kg
Kabellänge	3 m	Verpackungsbreite	165 mm
Energie		Verpackungstiefe	124 mm
Nominale Eingang Spannung *	208; 200 V	Verpackungshöhe	2040 mm
Stromstärke (maximal) *	30 A	Technische Details	
Nominale Ausgang Spannung	200 - 208 V	Nachhaltige Verpackung	✗
Ausgangsspannung	200 V; 208 V	Recycelte Verpackungsmaterialien	Recyclerter Karton
Ladekapazität	4992 VA	SCIP-Nummer	31346aed-552c-4a16-81d9-e683a383b6da
Zertifikate		Austauschbare Batterie	✓
Konformität von Elektro- und Elektronik-Altgeräten (WEEE)	✓	Bevorzugte Montageposition	no preference
Konformitätsbescheinigungen	RoHS, REACH, WEEE	Rücknahmesystem	✗
Zertifizierung	cUL listed; FCC part 15 class A; PSE	Verpackung ohne Einwegkunststoff	✗
		Logistikdaten	
		Ursprungsland	Indien
		Zolltarifnummer (TARIC)	8537109899

Nachhaltigkeit		Logistikdaten	
Nachhaltigkeitskonformität	✓	Gesamter Kohlendioxid-Fußabdruck (kg of CO2e)	2641,6506196672
Betriebsbedingungen			
Betriebstemperatur	-5 - 60 °C		
Temperaturbereich bei Lagerung	-25 - 65 °C		



0731304356264



731304356264

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.