



APC AP8887 Stromverteilereinheit (PDU) 42 AC-Ausgänge 0U
Schwarz

Marke : APC

Artikel-Code: AP8887

Produktname : AP8887

APC AP8887. PDU-Typen: Messgerät, Rack-Kapazität: 0U, Montage: Horizontal/Vertikal. Anzahl der AC-Ausgänge: 42 AC-Ausgänge, AC-Steckertypen: C13-Koppler, C19-Koppler, Eingang Verbindungstyp: IEC 60309 30 A 3P + N + E. Kabellänge: 1,82 m. Nominale Eingang Spannung: 400 3 phases, Stromstärke (maximal): 30 A, AC Eingangsfrequenz: 50 - 60 Hz. Konformitätsbescheinigungen: RoHS, REACH, WEEE, Zertifizierung: cUL listed; UL listed; VCCI class A



Design		Betriebsbedingungen	
PDU-Typen *	Messgerät	Temperaturbereich bei Lagerung	-25 - 65 °C
Rack-Kapazität *	0U	Relative Luftfeuchtigkeit in Betrieb	5 - 95%
Montage	Horizontal/Vertikal	Luftfeuchtigkeit bei Lagerung	5 - 95%
Produktfarbe	Schwarz	Höhe bei Betrieb	0 - 3000 m
Display	LCD	Höhe bei Lagerung	0 - 15000 m
Anschlüsse und Schnittstellen		Gewicht und Abmessungen	
Anzahl der AC-Ausgänge *	42 AC-Ausgänge	Breite	56 mm
AC-Steckertypen *	C13-Koppler, C19-Koppler	Tiefe	51 mm
Eingang Verbindungstyp	IEC 60309 30 A 3P + N + E	Höhe	1829 mm
Merkmale		Gewicht	9,6 kg
Kabellänge	1,82 m	Verpackungsdaten	
Energie		Paketgewicht	13,6 kg
Nominale Eingang Spannung *	400 3 phases	Verpackungsbreite	221 mm
AC Eingangsfrequenz	50 - 60 Hz	Verpackungstiefe	112 mm
Stromstärke (maximal) *	30 A	Verpackungshöhe	2149 mm
Nominale Ausgang Spannung	240 V	Technische Details	
Ausgangsspannung	240 V	Nachhaltige Verpackung	✗
Ladekapazität	17300 VA	Recycelte Verpackungsmaterialien	Recycelter Karton
Anzahl der Phasen	3	Austauschbare Batterie	✓
Maximaler Eingang Strom pro Phase	30 A	Halogenfrei	✗
Maximale Gesamtstromaufnahme pro Phase	24 A	Bevorzugte Montageposition	no preference
Energieschutzeigenschaften	Überlastschutz	Rücknahmesystem	✗
Zertifikate		Verpackung ohne Einwegkunststoff	✗
Konformität von Elektro- und Elektronik-Altgeräten (WEEE)	✓	Logistikdaten	
Konformitätsbescheinigungen	RoHS, REACH, WEEE	Ursprungsland	Indien
Zertifizierung	cUL listed; UL listed; VCCI class A	Zolltarifnummer (TARIC)	8537109899

Betriebsbedingungen		Logistikdaten	
Betriebstemperatur	0 - 55 °C	Gesamter Kohlendioxid-Fußabdruck (kg of CO2e)	3030,2027956064



0731304292432



731304292432

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.