

2m USB-C-Ladekabel, Schraubensicherung, 240W (5A) PD EPR, USB 2.0
Laptop-Ladekabel, Nylon Geflochten, USB-IF zertifiziert, Robustes USB C
Schnellladekabel

Produkt-ID: S2CEPR2M-USBSL-CABLE



Connect a charger to a USB Power Delivery (PD) 3.1-enabled device, using this USB-C Charging Cable. The USB-C charger cord delivers up to 240W of Extended Power Range (EPR) Power Delivery and 5A output for fast charging. The connector markings enable quick visual identification, distinguishing this cable from other similar-looking or unmarked USB-C cables. Eliminate guesswork and always choose the appropriate Type-C cable to support full 240W charging.

Quality Construction

Designed for frequent use, the USB-C EPR Charging Cable features a rugged TPE outer jacket for increased wear resistance. The durable nickel-plated connectors are rated to operate beyond 10,000 insertion cycles, enhancing its durability and longevity.

Charge Mobile Devices On The Go

Charge a USB-C device with a USB-C wall charger, car charger, or power bank. The 3-foot (0.9-meter) USB Type-C cable is the ideal length for desk and mobile workstations, commuters, in-car use or to reduce clutter when syncing with a USB-C laptop.

Power a Laptop

With up to 5A of output, the USB-C Charger Cord supports up to 240W of Power Delivery to charge a USB-C laptop, or fast charge a tablet or smartphone. To use, connect the cable from a USB-C laptop to a USB-C wall charger.

Zertifikate Berichte und Kompatibilität



Anwendungen

Merkmale

- **USB-C EPR CHARGING CABLE:** Type-C cable supports Power Delivery 3.1 Extended Power Range (EPR); Up to 240W to high-power USB-C laptops; 10ft length provides extra reach; Connector markings identify data/power specs; Choose the right 240W cable at-a-glance
- **USB-IF CERTIFIED:** The USB C Cable is USB-IF certified with integrated E-marker chip, for consistent Power Delivery output to USB-C hosts and peripherals; When using certified cables, reliable performance and compatibility is guaranteed
- **QUALITY CONSTRUCTION:** Nickel-plated connectors rated beyond 10,000 insertions; Thicker 24/28AWG wire for consistent power; Withstands 120° bends; Braided Aluminum shield protects from EMI; Durable TPE outer jacket is halogen-free and RoHS compliant
- **ANWENDUNGEN:** Kompatibel mit USB-C Power Delivery-fähigen Geräten; Schraubensicherung für Laufwerksgehäuse und externe Speicher; ideal für Power Laptops z.B. 16" MacBook Pro/Max M-serie; bietet USB 2.0 für Datentransfer und Gerätesynchronisation
- **PERFORMANCE:** 240W/5A PD 3.1 EPR, 48V; Backward Compatible w/140W/100W/60W; USB 2.0 Type-C (480Mbps); 10-foot (3-meter) cable; Color: Black; O.D.: 0.16in (4.0mm); TPE Jacket w/Braided Aluminum Shield; NOTE: USB-C video (DP Alt Mode) is not supported

Hardware

Garantiebestimmungen	Lifetime
Steckverbinderplatten	Nickel
Typ der Kabelummantelung	Silicone with Braided Nylon

Leistung

MTBF	Rated beyond 10,000 insertions
------	--------------------------------

Steckverbinder

Steckverbinder A	1 - USB Type-C (24-pin) USB 2.0 (480Mbps)
Steckverbinder B	1 - USB Type-C (24-pin) USB 2.0 (480Mbps)

Strom

Power Delivery 240W

Umgebungsbedingungen

Betriebstemperatur 0°C - 50°C (32°F - 122°F)
Lagertemperatur -20°C - 70°C (-4°F - 158°F)
Feuchtigkeit 5% - 85%

Physische Eigenschaften

Farbe Schwarz
Steckverbinderart Gerade
Drahtstärke 30 AWG
Gehäusetyp ABS
Kabellänge 6.6 ft [2 m]
Außendurchmesser des Kabels 0.2 in [4.7 mm]
Produktlänge 6.6 ft [2.0 m]
Produktbreite 0.8 in [2.0 cm]
Produkthöhe 0.3 in [6.8 mm]
Produktgewicht 3.0 oz [84.0 g]

Verpackungsinformationen

Paketlänge 5.0 in [12.8 cm]
Paketbreite 8.7 in [22.0 cm]
Pakethöhe 0.7 in [1.8 cm]
Versandgewicht (Verpackung) 3.2 oz [90.0 g]

Verpackungsinhalt

Im Paket enthalten 1 - 2m USB-C-Ladekabel M/M - Seitenverriegelung

* Größe, Aussehen und Spezifikationen sind Änderungen ohne vorherige Ankündigung vorbehalten.

